



7704-DMS

7706-ULF

TECHNOLOGY COMPARISON

Technology Features	7704-DMS Dedicated Monitoring System	7706-ULF Integrated Fire Monitoring System
Dimensions	13" x 10" x 4.5"	18.5" 14.25" x 4.75"
Weight Without Battery	8.1 lbs	17 lbs
Battery	12 AH	14AH (2)
Antenna	3.3 dB Phantom w/ NMO mount	2.5 dB Rubber Duck
Number of Zones	6	6
Zone Types	6 inputs Type B	1 input Type A or Type B 5 inputs Type B
Visual Indicators	LCD (2 x 20 alphanumeric character)	LCD (2 x 16 Alphanumeric Character)
Annunciator	Integrated buzzer or remote	Remote
Smoke Detector Compatibility	2-wire	2-wire
NAC Power	0.5 amps	0.5 amps
Auxillary Power	✗	✓
Ports	1 Ethernet 2 USB	1 Ethernet
Current Consumption	Reference 7704-DMS Battery Calculator	Reference 7704-DMS Battery Calculator
NAC Patterns	Temporal & Cadence patterns	Temporal & Cadence patterns
Programming Interface	Web Browser Capable device accessible via smartphone, tablet, laptop or PC	Laptop via Ethernet using Potter programming software or integrated keypad
Certifications	Meets NFPA 72 Specifications Intertek (ETL) tested to UL 864 standards FDNY/ CALFire	Meets NFPA 72 Specifications UL tested to UL 864 standards CALFire